

IXIO-D INDUS

MOTION AND PRESENCE
SENSOR FOR AUTOMATIC
INDUSTRIAL DOORS


Commercial sheet



PROTECTION OF DOORS & USERS


DESCRIPTION

The **IXIO-D INDUS** combines two technologies - radar and infrared - to achieve a double goal: opening and protection. The **IXIO-D INDUS** protects automatic doors as well as those operating them. The **IXIO-D INDUS** radar senses any approaching movement towards the door, while the infrared technology senses the presence of people and objects in the area around the closing zone of the door. The infrared technology complements the measures stipulated by standard EN 12453.



PROTECTING THE DOOR

The radar monitors a large, adjustable area. Its responsiveness makes it ideal for opening and re-opening the door for fork-lift trucks and vehicle traffic. In this way, it helps to prevent the vehicles from colliding into the door, when approaching at a reasonable speed.




PROTECTING USERS

Two curtains of 24 (48 total), high-density infrared spots provide precise presence detection near the threshold area.

Provided on both sides of the door, this additional volumetric protection reduces the door's hold-time and therefore reduces the opening and closing time of the door.

POSITION OF THE CURTAINS


Four infrared spots, visible on the floor, appear during configuration. This means that the position of the first curtain is easy to adjust.



LCD SCREEN


Intuitive setup via the LCD screen with text and symbol display (LCD graphics).






High-speed door

APPLICATIONS




**Detection area @ 3 m :
radar 4 m x 2 m ; infrared 3 m x 0,5 m**

DETECTION RANGE




**IXIO-S INDUS
Infrared sensor**

IXIO RANGE




Bracket accessory

ACCESSORIES



Rain accessory



Spotfinder

PERFORMANCE

- Motion and presence sensor for people and vehicles
- Unidirectional radar detects approach only
- Stable and reproducible opening area
- Reliable protection due to the double presence curtain
- Ideal solution for interior doors with an opening height of up to 4 m

APPLICATIONS

- Motion and presence detection for industrial doors

DESIGNED FOR INDUSTRIAL ENVIRONMENTS

- Reliable detection in sensitive environments

EASY INSTALLATION

- Intuitive configuration via LCD display and/or a BEA remote control
- Graphic LCD screen with language selection
- Lateral orientation of the radar antenna with a range of -15° to +15°
- 4 visible red spots on the floor for simplified setup of the presence curtain
- Plug, push & go
- 10 m cable

VERSIONS

- **IXIO-DO1 i** : Opening and presence
- **IXIO-DT1 i** : Opening and safety (external monitoring available)

TECHNICAL SPECIFICATIONS - IXIO-DO1 i

Technology	Microwave doppler radar Transmitter frequency: 24.150 GHz Transmitter radiated power: < 20 dBm EIRP Transmitter power density: < 5 mW/cm ²	Active infrared with background analysis Spot: 5 cm x 5 cm (typ) Number of spots: max. 24 per curtain Number of curtains: 2
Detection mode	Motion	Presence
Detection field	4.5 m x 2.5 m*	3.5 m x 0.5 m *
Tilt angle	15 ° - 45 °	-7 ° - +4 ° (adjustable)
Output	Solid-state-relay (potential and polarity free) Max. contact current: 100 mA Max. contact voltage: 42 V AC/DC	Solid-state-relay (potential and polarity free) Max. contact current: 100 mA Max. contact voltage: 42 V AC/DC
Hold time output signal	from 0.5 s to 9 s (adjustable)	from 0.3 s to 1 s (not adjustable)
Min. detection speed/ Typical response time	5 cm/s	< 200 ms (max. 500 ms)
LED signals	Green	Red
Mains frequency	50 to 60 Hz	
Supply voltage	12V - 24V AC +/- 10 % 12V - 30V DC - 5%/+10% (to be operated from SELV compatible power supplies only)	
Mounting height	2 m to 4 m **	
Dimensions	269.3 mm (L) x 57.3 mm (H) x 57.9 mm (W)	
Materials/ colour	ABS + LURAN S/ Black or white	
Temperature range	-25°C to +55°C; 0-95% relative humidity, non condensing	
Protection degree	IP54	
Norm conformity	R&TTE 1999/5/EC; LVD 2006/95/EC; RoHS 2 2011/65/EU	

*Specifications are subject to changes without prior notice.
* at 3.5 m mounting height ** depending on size and nature of the target*

DISCLAIMER This document as well as all other enclosed documents (quotation / specification / other) are provided «as is» without warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. / Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. / BEA has the right without liability to change descriptions and specifications at any time. / Prices, shipping and availability are subject to change without prior notice.

