

In compliance with the following Council Directives

1999/5/EC: **R&TTE Directive**
2006/95/EC: **Low Voltage Directive**
2011/65/EU: **RoHS 2 Directive**

We, manufacturer: **BEA SA**
 LIEGE Science Park
 Allée des Noisetiers 5
 B-4031 ANGLEUR
 Belgium



declare under our sole responsibility that the following product(s)

EAS RF Receiver
 Key fob transmitters
 Push plate transmitter 9V

to which this declaration relates are in conformity with the relevant provisions of the following standard(s) or other normative document(s):

EN 300 330-2 2010-12	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz Part 2: Harmonized EN under article 3.2 of the R&TTE Directive
EN 301 489 -1 & 3 2011-09 2013-08	ElectroMagnetic Compatibility and Radio spectrum Matters (ERM) ElectroMagnetic Compatibility (EMC) standard for radio equipment and services Part 1: Common technical requirements Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 40 GHz.
EN 60950-1 2013-05	Information Technology Equipment – Safety Part 1: General Requirements

The technical information is maintained at BEA SA and includes the following document(s):

Technical Construction File N° TCF063

We, the undersigned, hereby declare that the equipment specified above conforms to the above Council Directive(s) and Standard(s).

Manufacturer:

Pierre GARDIER (Authorised representative)
R&D Manager
October, 2014

Elmar KOCH
Managing Director
October, 2014

EAS RF ADDITIONAL PRODUCT INFORMATION

IMPORTANT INFORMATION CONCERNING THE USE OF THE TRANSMITTERS

- Characteristics key fob transmitter:

Transmitter frequency:	433 MHz \pm 0.1MHz
Operating voltage:	3 V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C

- Characteristics transmitter for push plates 3V:

Transmitter frequency:	433 MHz \pm 0.1MHz
Operating voltage:	3 V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C

- Characteristics transmitter for push plates 9V:

Transmitter frequency:	433 MHz \pm 0.1MHz
Operating voltage:	9V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C