

IXIO-D

OPENING AND SAFETY SENSOR FOR AUTOMATIC SLIDING DOORS

Commercial sheet




THE SECOND-GENERATION DUAL SENSOR

DESCRIPTION

The **IXIO-D** is a sensor which combines radar technology for the activation of the door with infrared technology for the user protection. The unidirectional radar enables energy savings to be made. The three-dimensional infrared curtain protects people from any contact with the doors.

COMPLIANT WITH
EN 16005/DIN 18650/AS 5007



UNIDIRECTIONAL

Due to the unidirectionality, the duration of the door opening cycle is shorter, which reduces heat loss from the building and saves energy. This also optimises the "airlock" function.



LCD

Intuitive configuration with an LCD screen with an LCD screen displaying texts and symbols (LCD graphics).



VIRTUAL BUTTON


IXIO-D is equipped with a special function to open the door with a simple hand wave. Eliminating the need for physical touch and complementing the current standards on touch-less solution.



INFRARED CURTAINS


48 high-density infrared spotlights from 2 curtains protect users from any contact with the doors.

A 32-bit microprocessor optimises the processing of information coming from the environment, ensuring a stable performance throughout the year.




SAFETY

4 red spotlights visible on the ground to adjust the angle of the failsafe curtain.






Single leaf sliding doors



Double leaf sliding doors

Area detection radar 4 m x 2 m @ 2.2 m
infrared 2,2 m x 0,5 m @ 2,2 m**IXIO-S**Presence sensor with infrared technology
for the safety of sliding doors**IXIO-M**Motion sensor with radar technology
for the opening automatic doors**APPLICATIONS**

- Opening and safety of linear, telescopic and curved automatic sliding doors.

EASE OF INSTALLATION

- Intuitive configuration thanks to an LCD screen and/or a BEA remote control.
- LCD graphics screen with choice of language.
- 10 adjustment options for the IR curtains.
- Lateral orientation from -15° to +15° for the radar antenna.
- 4 infrared spotlights visible on the ground for the easy adjustment of the failsafe curtain.
- Plug, push & go.

VERSIONS

- **IXIO-DT1**: dual sensor with combined technologies and self-monitoring.
- **IXIO-DT3**: dual sensor with combined technologies for emergency doors and standard doors. 3-in-1 product with choice of 3 types of output (current/frequency/relay).
- **IXIO-DP1**: dual sensor with combined technologies for pulsed safety door controllers.
- **IXIO-DP3**: dual sensor with combined technologies for emergency doors and standard doors with pulsed safety door control.

ACCESSORIES

Bracket accessory

Ceiling accessory

Spotfinder

TECHNICAL SPECIFICATIONS

Detection mode	Motion	Presence
Technology	Microwave doppler radar	Active infrared with background analysis
Output	Solid-state-relay (potential and polarity free)	Solid-state-relay (potential and polarity free)
	Frequency output* (f = 100 Hz +/- 10%)	Pulse output**
	Current source output*	
Test input	Sensitivity : Low : < 1 V; High : > 10 V	
Supply voltage	12 V - 24 V AC +/-10%; 12 V - 30 V DC +/- 10%	
Mounting height	2 m to 3,5 m (local regulations may have an impact on the acceptable mounting height)	
Temperature range	-25°C to +55°C; 0-95% relative humidity, non condensing	
Degree of protection	IP54	
Applicable directives /Norms	R&TTE 1999/5/EC; EMC 2004/108/EC; MD 2006/42/EC; RoHS 2002/95/EC EN 12978; EN ISO 13849-1:2008 PL «d» CAT. 2***/»c» CAT. 2****; EN 16005:2012 Chapter 4.6.8.; DIN 18650-1:2010 Chapter 5.7.4. ; AutSchR***	

Specifications are subject to change without prior notice.

* DT3/DP3 **DP1/DP3

*** Only applicable for frequency and current source output

**** Under the condition that the door control system monitors the sensor at least once per door cycle

DISCLAIMER This document as well as all other enclosed documents (quotation / specification / other) are provided «as is» without warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. / Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. / BEA has the right without liability to change descriptions and specifications at any time. / Prices, shipping and availability are subject to change without prior notice.

